

EVERLUBE[®] PRODUCTS

SAFETY DATA SHEET

EVERLUBE 6110 BLACK
Page 1 of 10

1. IDENTIFICATION:

PRODUCT NAME: EVERLUBE 6110 BLACK
PRODUCT CODE: PEV6110BK
PRODUCT USE.: Low Friction Coating

HMIS CODES H F R P
2*3 0 G

Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300
INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800
NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR
DATE PREPARED: 4/27/2021

2. HAZARDS IDENTIFICATION



CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2
Acute Toxicity, Dermal - Category 4
Acute Toxicity, Inhalation - Category 4
Acute Toxicity, Oral - Category 4
Aspiration Hazard - Category 1
Carcinogenicity - Category 2
Serious Eye Damage - Category 1
Reproductive Toxicity - Category 1
Skin Corrosion/Irritation - Category 2
Skin Sensitization - Category 1
Specific target organ toxicity, repeated exposure - Category 2
Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENTS:

H225-Highly flammable liquid and vapors
H304-May be fatal if swallowed and enters airways
H312-Harmful in contact with skin.
H315-Causes skin irritation
H317-May cause an allergic skin reaction
H318-Causes serious eye damage.
H332-Harmful if inhaled
H335-May cause respiratory irritation
H336-May cause drowsiness or dizziness
H351-Suspected of causing cancer
H360-May damage fertility or the unborn child.
H373-May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

PRECAUTIONARY STATEMENTS:

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking
 P242-Use only non-sparking tools.
 P280-Wear protective gloves/eye protection/face protection.
 P403-P233-Store in well-ventilated place. Keep container tightly closed.
 P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	% BY WT.
EPON RESIN	25036-25-3	15% - 20%
ACGIH TLV TWA-10 mg/m3 (inhalable particulate) OSHA PEL TWA-5 mg/m3 (respirable particulate) OSHA PEL TWA-15 mg/m3 (total dust) LD 50 Oral Rat >2,000 mg/kg LD 50 Dermal Rat >2,000 mg/kg		
XYLENE	1330-20-7	15% - 20%
ACGIH TWA: 100 PPM ACGIH STEL: 150 PPM OSHA Z-1 TWA: 100 PPM OSHA Z-1 435 mg/m3 LD50: ORAL 3,523 mg/kg (rat) LC50 INHALATION 6700 ppm (rat) 4hr EC50 ALGAE 4.36 mg/l 73 hr IC50 DAPHNIA 1 mg/l 24hr LC50 FISH 2.6 mg/l 96hr		
METHYL ISOBUTYL KETONE	108-10-1	10% - 15%
ACGIH TWA: 20 ppm ACGIH STEL: 75 ppm NIOSH REL: 50 ppm NIOSH REL: 205 mg/m3 NIOSH STEL: 75 ppm NIOSH STEL: 300 mg/m3 OSHA Z1-TWA100 ppm OSHA Z1-410 mg/m3 OSHA P0-TWA 50 ppm OSHA P0-205 mg/m3 OSHA P0-stel 75 ppm OSHA 300 mg/m3 LD50 RAT ORAL: 2080 mg/kg LD50 INHALATION RAT: >2000 PPM, 4 hr LC50 RAT INHALATION 8.L2-16.4 mg/l LC50 FISH >179 mg/l 96h EC50 AQUATIC INVERTEBRATES >200 mg/l 48h EC50 ALGAE 400 mg/l 95h		
ETHANOL	64-17-5	10% - 15%
OSHA PEL 1000.000 ppm TWA NIOSH REL 1,000 ppm TWA NIOSH REL 1,900 mg/m3 OSHA Z-1 1,000 ppm TWA OSHA Z-1 1,900 mg/m3 ACGIH 1,000 ppm STEL LD50 ORAL 7060 mg/kg (rat) LC 50 INHALATION 124.7 mg/l (rat) LC50 FISH 15,300 mg/l 96h EC50 DAPHNIA 5,012mg/l 48hr EC50 ALGAE 275 mg/l 72 hr		
TOLUENE	108-88-3	5% - 10%

SAFETY DATA SHEET

OSHA PEL 200.00 PPM-TWA		
OSHA PEL 300.000 PPM-CEILING		
OSHA VPEL 100.000 PPM-TWA		
OSHA VPEL 150.000 PPM-STEL (SKIN)		
ACGIH TLV 50.000 PPM-TWA (SKIN)		
ACGIH TLV 150.000 PPM-STEL (SKIN)		
LD 50 ORAL RAT: 2.6 g/kg		
LC 50 INHALATION RAT: 8000 PPM; 4 h		
LD 50 DERMAL RABBIT: 12,124 mg/kg		
LC50 FISH 7.63 mg/l 96 h		
EC50 INVERTEBRATES 8 mg/l 24 h		
EC50 ALGAE 10 mg/l 24h		
N-BUTANOL	71-36-3	5% - 10%
ACGIH TWA 20 PPM		
NIOSH REL 50 PPM		
NIOSH REL 150 mg/m3		
OSHA Z1 100 PPM - TWA		
OSHA Z1 300 mg/m3		
LC50 INHALATION 8000ppm (24.24 mg/l) (rat)		
OSHA P0 50 PPM - CEILING		
OSHA P0 150 mg/m3		
LD50 ORAL 790 mg/kg (rat)		
LC50 INHALATION >8000 PPM (rat)		
LD50 DERMAL 3.430 mg/kg (Rabbit)		
LC50 FISH 1,376 mg/l 96 h		
EC50 AQUATIC INVERTEBRATES 1,328 mg/l 48h		
EC50 ALGAE 225 mg/l 96 h		
NOEC AQUATIC INVERTEBRATES 4.1 mg/l 21d		
EC50 BACTERIA 4,390 mg/l 17h		
N-METHYL-2-PYRROLIDONE	872-50-4	0% - 5%
ACGIH BEI: 100 mg/l		
US WEEL 10 ppm TWA		
LD50 ORAL-4150 mg/kg (rat)		
LC50 INHALATION->5.1 mg/l 4h		
LD50 DERMAL: >5000 mg/kg (rat)		
LC50 FISH >100 mg/l 96h		
EC50 DAPHNIA >100 mg/l 24h		
EC50 ALGAE >100 mg/l 72h		
LC50 BACTERIA 9,000 mg/l		
PINE OIL	8002-09-3	0% - 5%
LD50 ORAL (RAT): 3840 mg/kg 14 days		
LD 50 DERMAL (RABBIT): >5000 mg/kg 14 days		
EC50 ALGAE 8 mg/l, 72 hr		
EC50 DAPHNIA 1.36 mg/lm 48 hr		
EC50 FISH 0.71 mg/l, 96 hr		
ETHYL BENZENE	100-41-4	0% - 5%
ACGIH: 20 ppm TWA		
OSHA 100 ppm TWA; 435 mg/m3 TWA		
OSHA 125 ppm STEL; 545 mg/m3 STEL		
NIOSH 100 ppm TWA; 435 mg/m3 TWA		
NIOSH 125 ppm STEL; 545 mg/m3 STEL		
LD50 ORAL: 3500 mg/kg (rat)		
LC50 Inhalation 17.2 mg/l 4h (rat)		
LD50 Dermal 15354 mg/kg (rabbit)		
LC50 FISH: 11.0-18.0 mg/l 96 hr		
EC50 ALGAE 4.6 mg/l 72 hr		
EC50 DAPHNIA 18.-2.5 mg/l 48 hr		
CARBON BLACK	1333-86-4	0% - 5%

SAFETY DATA SHEET

ACGIH-TLV: 3.0 mg/m³ TWA (INHALABLE)
 OSHA-PEL: 3.5 mg/m³ TWA
 LD50 ORAL: >8000 mg/kg (Rat)
 LC50 FISH >1,000 mg/l 96hr
 EC50 DAPHNIA >5,600 mg/l 24 hr
 EC50 ALGAE >10,000 mg/l 72 hr

PM ACETATE	108-65-6	0% - 5%
USWHEEL TWA 50ppm		
LD50 ORAL 8,532 mg/kg (rat)		
LD50: DERMAL >5000 mg/kg (rabbit)		
LC50 FISH 100 mg/l 96h		
EC50 DAPHNIA 500 mg/l 48h		
EC50 ALGAE 1,000 mg/l 96h		
2 METHYL IMIDAZOLE	693-98-1	0% - 5%
LD50 ORAL MOUSE: 1400 mg/kg		
LC50 FISH: 286 mg/l 96 hr		

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point (Degree F): 40 F

Flash Point Method: TCC

Explosive Limits:

Upper explosive limit: 36.0

Lower explosive limit: 1.0% (V)

Hazardous Combustion Products:

Carbon, Fluorine, or their compounds

Extinguishing Media:

CO₂, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill,

SAFETY DATA SHEET

and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:**Respiratory Protection:**

In case of inadequate ventilation, wear respirator protection.

SAFETY DATA SHEET

Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas).....: Data not available
 Boiling Point: 173 F
 Melting Point: Data not available
 VOC.....: 685 grams/liter
 Freezing Point: Data not available
 Flash Point: 40 F
 Vapor Pressure: None known
 Vapor Density: Heavier than air.
 Solubility in Water: Insoluble
 Density.....: 8.6 lb/gl
 Evaporation Rate: Faster than n-Butyl Acetate.
Explosive Limits:
 Upper Explosive Limit: 36.0
 Lower Explosive Limit: 1.0% (V)
 Specific Gravity: 1.03282
 PH: None known
 Volatile (% by Weight).....: 65%
 Appearance and Odor: Black liquid, organic solvent odor
 Odor Threshold: Not applicable
 Viscosity: Not applicable
 Partition Coefficient.....: Data not available
 Decomposition Temperature ...: Data not available
 Autoignition temperature.....: Data not available

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):
 Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released:
 Carbon, Fluorine, or their compounds

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None known

SAFETY DATA SHEET

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer):
Group 2A-Probably carcinogenic to humans

NTP (National Toxicology Program):
None known

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

May cause respiratory irritation
May cause drowsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

EVERLUBE® PRODUCTS
SAFETY DATA SHEET

UN Number:

UN 1263

UN Shipping Name:

PAINT RELATED MATERIAL

Transport Hazard Class:

Class 3



Packing Group:

Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant:

None known

Special Precautions for User:

None known

15. Regulatory Information

U.S. Federal Regulations:

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXEMPT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
EPON RESIN	25036-25-3	15% - 20%
XYLENE	1330-20-7	15% - 20%
METHYL ISOBUTYL KETONE	108-10-1	10% - 15%
TOLUENE	108-88-3	5% - 10%
N-BUTANOL	71-36-3	5% - 10%
N-METHYL-2-PYRROLIDONE	872-50-4	0% - 5%
PINE OIL	8002-09-3	0% - 5%
ETHYL BENZENE	100-41-4	0% - 5%
CARBON BLACK	1333-86-4	0% - 5%
ISOPROPANOL	67-63-0	0% - 5%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS Classification:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

DATE OF PREPARATION: 4/27/2021

KEY/LEGEND:

ACGIH: American Conference of Governmental Industrial Hygienists
ADR: International Carriage of Dangerous Goods by Road
RID: International Carriage of Dangerous Goods by Rail
CAS: Chemical Abstracts Service
CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act
DOT: Department of Transportation
HMIS: Hazardous Materials Identification System
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IDL: Immediately Dangerous to Life
IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization
LC: Lethal Concentration
LD: Lethal Dose
NIOSH: National Institute for Occupational Safety & Health
OSHA: Occupational Safety & Health Administration
PPM: Parts Per Million
REL: Recommended Exposure Limit
SARA: Superfund Amendments and Reauthorization Act
STEL: Short-term Exposure Limits
STOT: Specific Target Organ Toxicity
TLV: Threshold Limit Value
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average
VOC: Volatile Organic Compounds
WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN

SAFETY DATA SHEET

USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com