

1. IDENTIFICATION:

PRODUCT NAME: EVERLUBE 6112  
PRODUCT CODE: PEV6112  
PRODUCT USE.: Low Friction Coating  
Manufacturer:

HMIS CODES H F R P  
2\*3 0 C

EVERLUBE PRODUCTS  
100 COOPER CIRCLE  
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300  
INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800  
NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR  
DATE PREPARED: 4/27/2021

2. HAZARDS IDENTIFICATION



CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2  
Acute Toxicity, Dermal - Category 4  
Acute Toxicity, Inhalation - Category 4  
Acute Toxicity, Oral - Category 4  
Aspiration Hazard - Category 1  
Carcinogenicity - Category 1  
Serious Eye Irritation - Category 2  
Reproductive Toxicity - Category 1  
Skin Corrosion/Irritation - Category 2  
Skin Sensitization - Category 1  
Specific target organ toxicity, repeated exposure - Category 2  
Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H225-Highly flammable liquid and vapors  
H304-May be fatal if swallowed and enters airways  
H312-Harmful in contact with skin.  
H315-Causes skin irritation  
H317-May cause an allergic skin reaction  
H319-Causes serious eye irritation  
H332-Harmful if inhaled  
H335-May cause respiratory irritation  
H336-May cause drowsiness or dizziness  
H350-May cause cancer  
H360-May damage fertility or the unborn child.  
H373-May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

## SAFETY DATA SHEET

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking  
 P242-Use only non-sparking tools.  
 P280-Wear protective gloves/eye protection/face protection.  
 P403-P233-Store in well-ventilated place. Keep container tightly closed.  
 P501-Dispose of contents/container in accordance with local/regional/national/regulation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	% BY WT.
EPON RESIN	25036-25-3	15% - 20%
ACGIH TLV TWA-10 mg/m3 (inhalable particulate)		
OSHA PEL TWA-5 mg/m3 (respirable particulate)		
OSHA PEL TWA-15 mg/m3 (total dust)		
LD 50 Oral Rat >2,000 mg/kg		
LD 50 Dermal Rat >2,000 mg/kg		
TOLUENE	108-88-3	15% - 20%
OSHA PEL 200.00 PPM-TWA		
OSHA PEL 300.000 PPM-CEILING		
OSHA VPEL 100.000 PPM-TWA		
OSHA VPEL 150.000 PPM-STEL (SKIN)		
ACGIH TLV 50.000 PPM-TWA (SKIN)		
ACGIH TLV 150.000 PPM-STEL (SKIN)		
LD 50 ORAL RAT: 2.6 g/kg		
LC 50 INHALATION RAT: 8000 PPM; 4 h		
LD 50 DERMAL RABBIT: 12,124 mg/kg		
LC50 FISH 7.63 mg/l 96 h		
EC50 INVERTEBRATES 8 mg/l 24 h		
EC50 ALGAE 10 mg/l 24h		
METHYL ISOBUTYL KETONE	108-10-1	5% - 10%
ACGIH TWA: 20 ppm		
ACGIH STEL: 75 ppm		
NIOSH REL: 50 ppm		
NIOSH REL: 205 mg/m3		
NIOSH STEL: 75 ppm		
NIOSH STEL: 300 mg/m3		
OSHA Z1-TWA100 ppm		
OSHA Z1-410 mg/m3		
OSHA P0-TWA 50 ppm		
OSHA P0-205 mg/m3		
OSHA P0-stel 75 ppm		
OSHA 300 mg/m3		
LD50 RAT ORAL: 2080 mg/kg		
LD50 INHALATION RAT: >2000 PPM, 4 hr		
LC50 RAT INHALATION 8.L2-16.4 mg/l		
LC50 FISH >179 mg/l 96h		
EC50 AQUATIC INVERTEBRATES >200 mg/l 48h		
EC50 ALGAE 400 mg/l 95h		
ANTIMONY TRIOXIDE	1309-64-4	5% - 10%
ACGIH-TLV: 8 HR TWA-10 mg/m3, TOTAL		
ACGIH-TLV: 8 HR TWA-3 mg/3, RESPIRABLE		
OSHA-PEL: 8 HR TWA-15 mg/m3, TOTAL		
OSHA PEL: 8 HR TWA-5 mg/m3, RESPIRABLE		
LC50 INHALATION 4H RAT: >5.4 mg/l		
LD50 ORAL RAT: >5000 mg/kg		
ETHANOL	64-17-5	0% - 5%
OSHA PEL 1000.000 ppm TWA		
NIOSH REL 1,000 ppm TWA		
NIOSH REL 1,900 mg/m3		
OSHA Z-1 1,000 ppm TWA		

## SAFETY DATA SHEET

OSHA Z-1 1,900 mg/m <sup>3</sup>		
ACGIH 1,000 ppm STEL		
LD50 ORAL 7060 mg/kg (rat)		
LC 50 INHALATION 124.7 mg/l (rat)		
LC50 FISH 15,300 mg/l 96h		
EC50 DAPHNIA 5,012mg/l 48hr		
EC50 ALGAE 275 mg/l 72 hr		
<b>LEAD PHOSPHITE</b>	12141-20-7	0% - 5%
ACGIH TLV-TWA: 0.15 mg/m <sup>3</sup> (8 hrs), as Pb		
BLV: 50 mmg/100g blood		
OSHA PEL: 0.05 mg/m <sup>3</sup> , AS Pb		
<b>METHYL ETHYL KETONE</b>	78-93-3	0% - 5%
ACGIH TLV: 200 ppm		
ACGIH STEL: 300 ppm		
NIOSH REL: TWA 200 ppm		
NIOSH REL: TWA 590 mg/m <sup>3</sup>		
OSHA P0: TWA 200 ppm		
OSHA P0: TWA 590 mg/m <sup>3</sup>		
OSHA P0: STEL 300 ppm		
OSHA P0 STEL 885 mg/m <sup>3</sup>		
EC50 ALGAE ?100 mg/l 96 hr		
LD50 ORAL 3400.0 mg/kg (RATS)		
DC50 VAPORS 2000 PPM (RATS)		
LC50 FISH 100 mg/l 96 hr		
EC50 DAPHNIA >100 mg/l 48 hr		
<b>N-BUTANOL</b>	71-36-3	0% - 5%
ACGIH TWA 20 PPM		
NIOSH REL 50 PPM		
NIOSH REL 150 mg/m <sup>3</sup>		
OSHA Z1 100 PPM - TWA		
OSHA Z1 300 mg/m <sup>3</sup>		
LC50 INHALATIN 8000ppm (24.24 mg/l) (rat)		
OSHA P0 50 PPM - CEILING		
OSHA P0 150 mg/m <sup>3</sup>		
LD50 ORGAL 790 mg/kg (rat)		
LC50 INHALATION >8000 PPM (rat)		
LD50 DERMAL 3.430 mg/kg (Rabbit)		
LC50 FISH 1,376 mg/l 96 h		
EC50 AQUATIC INVERTEBRATES 1,328 mg/l 48h		
EC50 ALGAE 225 mg/l 96 h		
NOEC AQUATIC INVERTEBRATES 4.1 mg/l 21d		
EC50 BACTARIA 4,390 mg/l 17h		
<b>XYLENE</b>	1330-20-7	0% - 5%
ACGIH TWA: 100 PPM		
ACGIH STEL: 150 PPM		
OSHA Z-1 TWA: 100 PPM		
OSHA Z-1 435 mg/m <sup>3</sup>		
LD50: ORAL 3,523 mg/kg (rat)		
LC50 INHALATION 6700 ppm (rat) 4hr		
EC50 ALGAE 4.36 mg/l 73 hr		
IC50 DAPHNIA 1 mg/l 24hr		
LC50 FISH 2.6 mg/l 96hr		
<b>PINE OIL</b>	8002-09-3	0% - 5%
LD50 ORAL (RAT): 3840 mg/kg 14 days		
LD 50 DERMAL (RABBIT): >5000 mg/kg 14 days		
EC50 ALGAE 8 mg/l, 72 hr		
EC50 DAPHNIA 1.36 mg/lm 48 hr		
EC50 FISH 0.71 mg/l, 96 hr		

## SAFETY DATA SHEET

<p>N-METHYL-2-PYRROLIDONE            ACGIH BEI: 100 mg/l            US WEEL 10 ppm TWA            LD50 ORAL-4150 mg/kg (rat)            LC50 INHALATION-&gt;5.1 mg/l 4h            LD50 DERMAL: &gt;5000 mg/kg (rat)            LC50 FISH &gt;100 mg/l 96h            EC50 DAPHNIA &gt;100 mg/l 24h            EC50 ALGAE &gt;100 mg/l 72h            LC50 BACTERIA 9,000 mg/l</p>	872-50-4	0% - 5%
<p>CARBON BLACK            ACGIH-TLV: 3.0 mg/m3 TWA (INHALABLE)            OSHA-PEL: 3.5 mg/m3 TWA            LD50 ORAL: &gt;8000 mg/kg (Rat)            LC50 FISH &gt;1,000 mg/l 96hr            EC50 DAPHNIA &gt;5,600 mg/l 24 hr            EC50 ALGAE &gt;10,000 mg/l 72 hr</p>	1333-86-4	0% - 5%
<p>ETHYL BENZENE            ACGIH: 20 ppm TWA            OSHA 100 ppm TWA; 435 mg/m3 TWA            OSHA 125 ppm STEL; 545 mg/m3 STEL            NIOSH 100 ppm TWA; 435 mg/m3 TWA            NIOSH 125 ppm STEL; 545 mg/m3 STEL            LD50 ORAL: 3500 mg/kg (rat)            LC50 Inhalation 17.2 mg/l 4h (rat)            LD50 Dermal 15354 mg/kg (rabbit)            LC50 FISH: 11.0-18.0 mg/l 96 hr            EC50 ALGAE 4.6 mg/l 72 hr            EC50 DAPHNIA 18.-2.5 mg/l 48 hr</p>	100-41-4	0% - 5%
<p>PM ACETATE            USWEEL TWA 50ppm            LD50 ORAL 8,532 mg/kg (rat)            LD50: DERMAL &gt;5000 mg/kg (rabbit)            LC50 FISH 100 mg/l 96h            EC50 DAPHNIA 500 mg/l 48h            EC50 ALGAE 1,000 mg/l 96h</p>	108-65-6	0% - 5%

#### 4. First Aid Measures

---

**Eyes:**

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

**Skin:**

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

**Ingestion:**

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

**Inhalation:**

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

#### 5. Fire Fighting Measures

---

**Flammable Properties:**

**Flash Point (Degree F) : 16F**

**Flash Point Method : TCC**

## SAFETY DATA SHEET

**Explosive Limits:**

Upper explosive limit: 36.0

Lower explosive limit: 1.0% (V)

**Hazardous Combustion Products:**

Carbon, Sulfur, Antimony, Lead, or their compounds

**Extinguishing Media:**

CO<sub>2</sub>, foam, dry chemical or halon

**Firefighting Procedures:**

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

In case of fire, toxic fumes of lead oxide may be emitted.

### 6. Accidental Release Measures

---

**Small Spill:**

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

**Large Spill:**

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

**Environmental Precautions:**

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

### 7. Handling and Storage

---

**Handling:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

**Storage:**

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

### 8. Exposure Controls/Personal Protection

---

**Airborne Exposure Limits:**

## SAFETY DATA SHEET

Mixture, see section 3

### Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

### Personal Protective Equipment:



### Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

### Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

### Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

## 9. Physical and Chemical Properties

---

Flammability (solid, gas).....: Data not available  
 Boiling Point .....: 173 F  
 Melting Point .....: Data not available  
 VOC.....: 455 grams/liter  
 Freezing Point .....: Data not available  
 Flash Point .....: 16F  
 Vapor Pressure .....: Data not available  
 Vapor Density .....: Heavier than air.  
 Solubility in Water .....: Slightly Soluble  
 Density.....: 10.1 lb/gl  
 Evaporation Rate .....: Faster than n-Butyl Acetate.  
**Explosive Limits:**  
     Upper Explosive Limit .....: 36.0  
     Lower Explosive Limit .....: 1.0% (V)  
 Specific Gravity .....: 1.21296  
 PH .....: None known  
 Volatile (% by Weight).....: 45%  
 Appearance and Odor .....: Gray/Black liquid, organic solvent odor  
 Odor Threshold .....: Not applicable  
 Viscosity .....: Not applicable  
 Partition Coefficient.....: Data not available  
 Decomposition Temperature ...: Data not available  
 Autoignition temperature.....: Data not available

## 10. Stability and Reactivity

---

### Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

**Incompatibility:**

Oxidizers, Strong Acids or Alkalies.

**Hazardous Decomposition Products:**

Irritating and/or toxic fumes including the following may be released:  
Carbon, Sulfur, Antimony, Lead, or their compounds

**Hazardous Polymerization:**

Will not occur.

**11. Toxicological Information**

---

**Acute Toxicity Values:**

Mixture, see section 3 - Hazardous Ingredients

**Germ Cell Mutagenicity:**

None known

**Chronic/Carcinogenicity:**

IARC (International Agency for Research of Cancer):  
Group 1-Carcinogenic to humans

NTP (National Toxicology Program):

None known

**Reproductive Toxicity:**

Product contains chemical(s) that may damage fertility or  
the unborn child

**STOT-single exposure:**

May cause respiratory irritation  
May cause drowsiness or dizziness

**STOT-repeated exposure:**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:**

May be fatal if swallowed and enters airways

**Routes of Exposure:**

Skin contact, skin absorption, eye contact, inhalation

**12. Ecological Information**

---

**Environmental Fate:**

Do not allow product or runoff from fire control to enter storm or sanitary  
sewers, lakes, rivers, streams, or public waterways. Canadian and U.S.  
regulations require that environmental and/or other agencies be notified of a  
spill incident. The spill area must be cleaned and restored to the original  
condition or to the satisfaction of authorities.

**Environmental Toxicity:**

Data not available

**Persistence and Degradability:**

Data not available

## SAFETY DATA SHEET

**Bioaccumulative Potential:**

Data not available

**Mobility in Soil**

Data not available

**Other Adverse Effects:**

None known

**13. Disposal Considerations**

---

**Disposal Methods:**

Dispose of contents/container to: A licensed waste disposal facility.  
Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

**14. Transport Information**

---

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

**UN Number:**

UN 1263

**UN Shipping Name:**

PAINT RELATED MATERIAL

**Transport Hazard Class:**

Class 3

**Packing Group:**

Group II

**ENVIRONMENTAL HAZARDS:****Marine Pollutant:**

None known

**Special Precautions for User:**

None known

**15. Regulatory Information**

---

**U.S. Federal Regulations:****TSCA:**

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXEMPT FROM REQUIREMENTS

**CERCLA: SARA Hazard Category:****Section 313:**

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE



## SAFETY DATA SHEET

ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
EPON RESIN	25036-25-3	15% - 20%
TOLUENE	108-88-3	15% - 20%
METHYL ISOBUTYL KETONE	108-10-1	5% - 10%
ANTIMONY TRIOXIDE	1309-64-4	5% - 10%
LEAD PHOSPHITE	12141-20-7	0% - 5%
N-BUTANOL	71-36-3	0% - 5%
XYLENE	1330-20-7	0% - 5%
PINE OIL	8002-09-3	0% - 5%
N-METHYL-2-PYRROLIDONE	872-50-4	0% - 5%

**FRANK DODD SECTION 1502:**

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

**State Regulations:**

**California Prop 65:**

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**International Regulations:**

**WHMIS:**

B2, D2A, D2B,

**CEPA (Canadian Environmental Protection Act)**

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

**EINECS (European Inventory of Existing Chemical List)**

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

**16. Other Information**

**Date of Preparation: 4/27/2021**

**KEY/LEGEND**

- ACGIH: American Conference of Governmental Industrial Hygienists
- ADR: International Carriage of Dangerous Goods by Road
- RID: International Carriage of Dangerous Goods by Rail
- CAS: Chemical Abstracts Service
- CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act
- DOT: Department of Transportation
- HMIS: Hazardous Materials Identification System
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organization
- IDL: Immediately Dangerous to Life
- IMDG: International Maritime Dangerous Goods
- IMO: International Maritime Organization

## SAFETY DATA SHEET

LC: Lethal Concentration  
LD: Lethal Dose  
NIOSH: National Institute for Occupational Safety & Health  
OSHA: Occupational Safety & Health Administration  
PPM: Parts Per Million  
REL: Recommended Exposure Limit  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short-term Exposure Limits  
STOT: Specific Target Organ Toxicity  
TLV: Threshold Limit Value  
TSCA: Toxic Substances Control Act  
TWA: Time Weighted Average  
VOC: Volatile Organic Compounds  
WHMIS: Workplace Hazardous Materials Information System

### **Manufacturer Disclaimer:**

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

[www.everlubeproducts.com](http://www.everlubeproducts.com)