

MATERIAL SAFETY DATA SHEET
EVERLUBE 625

PRODUCT NAME: EVERLUBE 625
 PRODUCT CODE: PEV625

HMIS CODES H F R P
 2*3 0 G

1. MANUFACTURING IDENTIFICATION

EVERLUBE PRODUCTS
 100 COOPER CIRCLE
 PEACHTREE CITY, GA 30269
 EMERGENCY PHONE: CHEMTREC - 800-424-9300

DATE PREPARED: 7/19/2010
 INFORMATION PHONE: (770) 261-4800
 NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

2. HAZARDOUS INGREDIENTS

COMPONENT/EXPOSURE LIMITS	CAS#	% BY WT.

METHYL ETHYL KETONE	78-93-3	25% - 30%
OSHA PEL 200.000 PPM - TWA		
OSHA VPEL 200.000 PPM - TWA		
OSHA VPEL 300.000 PPM - STEL		
ACGIH TLV 200.000 PPM - TWA		
ACGIH TLV 300.000 PPM - STEL		
LD50-930 mg/m3 ORAL (rat)		
LD50 100 mg/kg ORAL (mouse)		
LD50 200 ul/kg DERMAL (rabbit)		
ETHANOL	64-17-5	20% - 25%
OSHA PEL 1000.000 ppm - TWA		
OSHA VPEL 1000.000 ppm - TWA		
ACGIH TLV 1000.000 ppm - TWA		
LD50 ORAL-7060 mg/kg (rat)		
LC 50 INHALATION-20000 ppm 10 hr (rat)		
PM ACETATE	108-65-6	5% - 10%
ACGIH TLV: NONE ESTABLISHED		
OSHA PEL: NONE ESTABLISHED		
EXPOSURE LIMITS: 100 PPM		
LD50 ORAL >10000 mg/kr (male rat)		
LD50 ORAL 8500 mg/kg (female rat)		
LD50 INHALATION 6h: >4345 ppm (male rat)		
LD50 DERMAL >5000 mg/kg (rabbit)		
MOLYBDENUM DISULFIDE	1317-33-5	0% - 5%
ACGIH TWA I 10 mg/m3		
ACGIH TWA R 3 mg/m3		
LD50/LC50: 500 mg Acute Oral (rats)		
ANTIMONY TRIOXIDE	1309-64-4	0% - 5%
ACGIH PEL-TWA: 0.5 mg/m3 as Sb		
ACGIH TLV TWA: 0.5 mg/m3 as Sb		
LD50/LC50:		
>2,000 mg/kg Acute Dermal (rabbit)		
>34,600 mg/kg Acute Oral (rat)		
3,250 mg/kg Acute Intraperitoneal (rat)		
172 mg/kg Acute Intraperitoneal (mouse)		
ISOPROPANOL	67-63-0	0% - 5%
OSHA PEL 400.000 ppm-TWA		
OSHA VPEL 400.000 ppm-TWA		

MATERIAL SAFETY DATA SHEET
EVERLUBE 625

Page 2 of 8

OSHA VPEL 500.000 ppm-STEL		
ACGIH TLV 200.000 ppm-TWA		
ACHIH TLV 400.000 ppm-STEL		
LD50 ORAL - 5840 mg/kg (rat)		
LD50 DERMAL-13000 mg/kg (rabbit)		
CARBON BLACK	1333-86-4	0% - 5%
ACGIH-TLV: 3.5 mg/m3 TWA		
OSHA-PEL: 3.5 mg/m3 TWA		
LD50 ORAL: >8000 mg/kg (Rat)		
BARIUM METABORATE	13701-59-2	0% - 5%
ACGIH TLV: 0.5 MG/M3		
OSHA PEL: 0.5 MG/M3		
PHENOL	108-95-2	0% - 5%
ACGIH TLV-TWA 5 ppm (Skin)		
OSHA PEL-TWA 5 ppm (skin)		
LD50 ORAL 410-650 mg/kg (rat)		
LC50 INHALATION: 900 mg/m3 (rat)		
METHYL ALCOHOL	67-56-1	0% - 5%
OSHA PEL 200.000 ppm-TWA		
OSHA VPEL 200.000 ppm-TWA (Skin)		
OSHA VPEL 500.000 ppm-STEL (Skin)		
ACGIH TLV 200.000 ppm-TWA (Skin)		
ACHIH TLV 250.000 ppm-STEL (Skin)		
LD50 ORAL 1000.0 mg/kg (man)		
LC50 VAPORS 1600 ppm (rats)		
XYLENE	1330-20-7	0% - 5%
ACGIH TLV: 100 PPM		
OSHA PEL: 100 PPM		
ACGIH STEL: 150 PPM		
LD50/LC50:		
LD50:>2000mg/kr (rat)		
LD50: >2000 mg/kr (rabbit)		
LD50: >5000 ppm/1 hour (rat)		
ETHYL BENZENE	100-41-4	0% - 5%
OSHA PEL 100 ppm-TWA		
OSHA VPEL 100 ppm-TWA		
OSHA VPEL 125 ppm-STEL		
ACGIH TLV 100 ppm-TWA		
ACGIH TLV 125 ppm-STEL		
LD50 ORAL: 3500 mg/kg (rat)		

3. HAZARDS IDENTIFICATION

POTENTIAL EFFECTS OF SHORT-TERM (ACUTE) EXPOSURE:

Processing fumes may cause irritation of the eyes and respiratory tract. Use with adequate ventilation. Avoid breathing process fumes.

EYE CONTACT:

This material can cause eye irritation.

SKIN CONTACT:

Prolonged and repeated contact with the skin can cause defatting and drying of the skin resulting in skin irritation and skin rash (dermatitis).

INHALATION:

Inhalation of high concentrations of solvents may cause narcotic

effects such as headaches, dizziness, nausea, vomiting and coma.

INGESTION:

May cause adverse health effects and can cause gastro-intestinal irritation.

POTENTIAL EFFECTS OF LONG-TERM (CHRONIC) EXPOSURE:

No specific information is available regarding long-term exposure to this material. Other information on any known toxic or chronic-health effects of the material or its ingredients can be found in Section 11 - Toxicological Information.

4. FIRST AID MEASURES

EYE CONTACT:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate Medical Assistance.

SKIN CONTACT:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used

Consult a doctor if irritation persists.

INHALATION:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain Medical Aid.

INGESTION:

Never give anything by mouth if the victim is semi-conscious, unconscious or convulsing.

Seek immediate medical attention.

Induce vomiting immediately by giving 2 glasses of water and stimulating the uvula with a finger.

NOTE TO PHYSICIANS:

The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 ml/Kg has been ingested, vomiting should be induced with supervision. If symptoms, such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:

Vapors may form, with air, an explosive mixture between lower and upper explosive limits.

FLASH POINT (DEGREES F.): 23 F
FLASH POINT METHOD: TCC
LOWER FLAMMABILITY LIMIT (% BY VOLUME)..: 1.5
UPPER FLAMMABILITY LIMIT (% BY VOLUME)..: 36.0
AUTO-IGNITION TEMPERATURE.....: n/a

HAZARDOUS DECOMPOSITON PRODUCTS:

Irritating and/or toxic fumes including the following may be released:
Carbon, Sulfur, Antimony, or their compounds

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Avoid accumulation of water. Product will float on water and may reignite on surface of water.

Closed containers may explode due to pressure build-up when exposed to extreme heat.

DO NOT cut, drill, grind or weld near containers even when empty. Residual product or vapours may ignite or explode.

Extinguish all nearby sources of ignition.

EXTINGUISHING MEDIA:

CO₂, foam, dry chemical or halon

FIREFIGHTING PROCEDURES / EQUIPMENT:

Extinguish all nearby sources of ignition.

Use water spray to cool containers and structures exposed to fire.

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Emergency personnel must wear the following protective equipment: self-contained breathing apparatus, protective clothing, safety goggles and boots.

Evacuate all personnel not related to emergency procedures.

ENVIRONMENTAL PRECAUTIONS:

Prevent the product or the wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

SPILL RESPONSE / CLEANUP:

SMALL SPILL:

Eliminate all sources of ignition, provide ventilation, contain spill and absorb with inert absorbent.

Issue warning "Flammable". Isolate the hazard area and restrict access.

Handle as highly flammable liquid.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Prevent the spill or wash from entering sewers or watercourses.

LARGE SPILL:

Remove by mechanical means and place in containers.

7. HANDLING AND STORAGE

SAFE HANDLING PROCEDURES:

Maintain good personal hygiene. Avoid breathing processing vapours. Avoid prolonged or repeated skin contact. Wash skin with soap and water after handling. Wash contaminated clothing before re-use.

STORAGE REQUIREMENTS / CONDITIONS TO AVOID:

Keep containers closed (when not in use).

Keep away from heat, sparks and flames.

Store in a cool, dry, well ventilated area away from incompatible materials.

Smoking in the area where this material is used should be strictly prohibited.

DO NOT cut, drill, grind or weld near containers even when empty. Residual product or vapours may ignite or explode.

INCOMPATIBLE MATERIALS:

Oxidisers, Strong Acids or Alkalies.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS:

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below the threshold limit values.

All ventilation equipment must be explosion proof.

For personal entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere. Make-up air should always be supplied to balance air exhausted.

Effective exhaust ventilation should always be provided to draw fumes, vapors or dust away from workers to prevent routine inhalation.

RESPIRATORY PROTECTION:

Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

SKIN PROTECTION AND GLOVES:

Use Chemically impermeable gloves (eg Neoprene or Nitrile) for skin protection.

EYE PROTECTION:

Use chemical Safety Glasses/Goggles and Faceshields. Contact lenses should not be worn without goggles.

OTHER PROTECTIVE EQUIPMENT:

Eye wash stations and safety showers in the workplace are recommended.

PERMISSIBLE EXPOSURE LEVELS:

EVERLUBE 625

PLEASE SEE SECTION 2, HAZARDOUS MATERIALS.

9. PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY: 1.0088
 POUNDS PER GALLON: 8.4 lb/gl
 VOLATILE (% BY VOLUME): Not available
 VOLATILE (% BY WEIGHT): 60%
 BOILING POINT (DEGREES F.): 150F to 200F
 VOC (EPA Method 24).....: 615 grams/liter
 MELTING POINT.....: Not Established.
 EVAPORATION RATE (BUTYL ACETATE=1): Faster than n-Butyl Acetate.
 VAPOR PRESSURE (MM HG AT 20°F.)...: Not Available.
 VAPOR DENSITY (AIR=1).....: Heavier than air.
 SOLUBILITY IN WATER: Slightly Soluble
 PH: Not Applicable.
 APPEARANCE AND ODOR: Black liquid, organic solvent odor

10. STABILITY AND REACTIVITY

STABILITY AND REACTIVITY:

Stable under normal conditions.

CONDITIONS TO AVOID:

Heat, sparks, open flames or other sources of ignition.

MATERIALS TO AVOID:

Oxidizers, Strong Acids or Alkalies.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

LD50 / LC50:

Please see Section 2, Hazardous Ingredients.

CARCINOGENICITY:

IARC-Yes

NTP-Yes

MUTAGENICITY:

None known.

SENSITIZATION TO MATERIAL:

None Known

CONDITIONS AGGRAVATED BY EXPOSURE:

May aggravate pre-existing skin or respiratory disorders (bronchitis, emphysema, hyper-reactivity) skin allergies, eczema.

SYNERGYSTIC MATERIALS:

None known

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or

MATERIAL SAFETY DATA SHEET
EVERLUBE 625

other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

AQUATIC TOXICITY:

Not known to be a marine pollutant

13. WASTE DISPOSAL

WASTE MANAGEMENT:

Waste management priorities (depending on volumes and concentration of waste) are: 1. Recycle (reprocess), 2. Energy recovery (cement kilns, thermal power generation), 3. Incineration, 4. Disposal at a licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority

14. TRANSPORT INFORMATION

TDG: PAINT RELATED MATERIAL
CLASS 3, UN1263, PACKING GROUP II

15. REGULATORY INFORMATION

WHMIS CLASSIFICATION:

B2, D2A, D2B,

CANADIAN WHMIS:

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATIONS (CPR), AND THIS MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

OSHA REGULATED: YES

SARA:

IF THIS MATERIAL HAS ANY COMPONENTS WHICH ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THEN THERE ARE NO REPORTABLE COMPONENTS.

COMPONENTS REPORTABLE UNDER SARA 313: CAS# **% BY WT.**

COMPONENTS REPORTABLE UNDER SARA 313: CAS#	% BY WT.
METHYL ETHYL KETONE	78-93-3 25% - 30%
ETHANOL	64-17-5 20% - 25%
ANTIMONY TRIOXIDE	1309-64-4 0% - 5%
CARBON BLACK	1333-86-4 0% - 5%
BARIUM METABORATE	13701-59-2 0% - 5%
PHENOL	108-95-2 0% - 5%
METHYL ALCOHOL	67-56-1 0% - 5%
ZINC OXIDE	1314-13-2 0% - 5%
CRESOLS	1319-77-3 0% - 5%
XYLENE	1330-20-7 0% - 5%
ETHYL BENZENE	100-41-4 0% - 5%

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXEMPT FROM TSCA INVENTORY REQUIREMENTS

16. OTHER INFORMATION

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF

MATERIAL SAFETY DATA SHEET

Page 8 of 8

EVERLUBE 625

PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER IT IS THE USER'S RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS MSDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS MSDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOME HE KNOWS OR BELIEVES WILL USE THIS MATERIAL.

www.everlubeproducts.com