EVERLUBE 810 DILUTED Page 1 of 8

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

1. IDENTIFICATION:

PRODUCT NAME: EVERLUBE 810 DILUTED PRODUCT CODE: PEV810D PRODUCT USE.: Low Friction Coating HMIS CODES H F R P 2*3 0 G

Manufacturer:

EVERLUBE PRODUCTS 100 COOPER CIRCLE PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300 INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800 NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR DATE PREPARED: 7/25/2019

2. HAZARDS INDENTIFICATION



CLASSIFICATION: Highly Flammable Liquid and Vapors - Category 2 Aspiration Hazard - Category 1 Carcinogenicity - Category 2 Serious Eye Irritation - Category 2 Germ Cell Mutagenicity - Category 1 Reproductive Toxicity - Category 2 Skin Corrosion/Irritation - Category 2 Specific target organ toxicity, repeated exposure - Category 1 Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD: DANGER

HAZARDS STATEMENT:

H225-Highly flammable liquid and vapors H304-May be fatal if swallowed and enters airways H315-Causes skin irritation H319-Causes serious eye irritation H335-May cause respiratory irritation H336-May cause drowsiness or dizziness H340-May cause genetic defects H351-Suspected of causing cancer H361-Suspected of damaging fertility or the unborn child. H372-Causes damage to organs through prolonged and repeated exposure

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood. P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking P242-Use only non-sparking tools. P280-Wear protective gloves/eye protection/face protection. P403-P233-Store in well-ventilated place. Keep container tightly closed.

EVERLUBE 810 DILUTED Page 2 of 8

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS# %	BY WT.
TOLUENE	108-88-3	80 - 85%
OSHA PEL 200.00 PPM-TWA		
OSHA PEL 300.000 PPM-CEILING		
OSHA VPEL 100.000 PPM-TWA		
OSHA VPEL 150.000 PPM-STEL (SKIN)		
ACGIH TLV 50.000 PPM-TWA (SKIN)		
ACGIH TLV 150.000 PPM-STEL (SKIN)		
LD 50 ORAL RAT: 2.6 g/kg		
LC 50 INHALATION RAT: 8000 PPM; 4 h		
LD 50 DERMAL RABBIT: 12,124 mg/kg		
LC50 FISH 7.63 mg/l 96 h		
EC50 INVERTEBRATES 8 mg/l 24 h		
EC50 ALGAE 10 mg/l 24h		
VM&P NAPHTHA	64742-89-8	0% - 5%
OSHA Z1 TWA 500 PPM	01/12 00 0	
OSHA Z1 TWA 2,000 mg/m3		
OSHA PO TWA 400 PPM		
OSHA PO TWA 1,600 mg/m3		
LD 50 ORAL $>5000 \text{ mg/kg}$ (rat)		
LD50 DERMAL >2000 mg/kg (rabbit)		
LC50 FISH 8.2 mg/l 96h		
EC50 ACQUATIC INVERTEBRES 4.5 mg/l 48h		
EC50 ALGAE3.7 mg/l 96h		
BENZENE	71-43-2	0% - 5%
LD50 ORAL >5,000 mg/kg (rat)		
LD50 DERMAL >3,000 mg/kg (rabbit)		
LD50 INGESTION >2000 mg/kg (rat)		
ETHYL BENZENE	100-41-4	0% - 5%
ACGIH: 20 ppm TWA		
OSHA 100 ppm TWA; 435 mg/m3 TWA		
OSHA 125 ppm STEL; 545 mg/m3 STEL		
NIOSH 100 ppm TWA; 435 mg/m3 TWA		
NIOSH 125 ppm STEL; 545 mg/m3 STEL		
LD50 ORAL: 3500 mg/kg (rat)		
LC50 Inhalation 17.2 mg/l 4h (rat)		
LD50 Dermal 15354 mg/kg (rabbit)		
LC50 FISH: 11.0-18.0 mg/l 96 hr		
EC50 ALGAE 4.6 mg/l 72 hr		
EC50 DAPHNIA 182.5 mg/l 48 hr		

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Hazardous Combustion Products: Carbon, Sulfur, Silicon, or their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:



Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas):	Data not available
Boiling Point	194 F
Melting Point	Data not available
VOC:	810 grams/liter
Freezing Point	Data not available
Flash Point	40 F
Vapor Pressure	Data not available
Vapor Density	Heavier than air.
Solubility in Water	Slightly Soluble
Density:	7.5 lb/gl
Evaporation Rate	Faster than n-Butyl Acetate.
Explosive Limits:	
Upper Explosive Limit:	7.0
Lower Explosive Limit:	0.9
Specific Gravity	.90071
PH	None known
Volatile (% by Weight):	90%
Appearance and Odor	Gray/Black liquid, organic solvent odor
Odor Threshold	Not applicable
Viscosity	
Partition Coefficient:	Data not available
Decomposition Temperature:	Data not available

Autoignition temperature....: Data not available

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid): Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Carbon, Sulfur, Silicon, or their compounds

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

May cause genetic defects

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer): Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): None known

Reproductive Toxicity:

Product contains chemical(s) suspected of damaging fertility/unborn child

STOT-single exposure:

May cause drowsiness or dizziness

STOT-repeated exposure:

Causes damage to organs through prolonged or repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number: UN 1263

UN Shipping Name: PAINT RELATED MATERIAL

Transport Hazard Class:

Class 3



Packing Group: Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant: None known

Special Precautions for User: None known

15. Regulatory Information

U.S. Federal Regulations:

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINCT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:



Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	8 BY WT.
TOLUENE	108-88-3	80 - 85%
VM&P NAPHTHA	64742-89-8	0% - 5%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 7/25/2019

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists ADR: International Carriage of Dangerous Goods by Road RID: International Carriage of Dangerous Goods by Rail CAS: Chemical Abstracts Service CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act DOT: Department of Transportation HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization IDL: Immediately Dangerous to Life IMDG: International Maritime Dangerous Goods IMO: International Maritime Organization LC: Lethal Concentration LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health OSHA: Occupational Safety & Health Administration PPM: Parts Per Million REL: Recommended Exposure Limit SARA: Superfund Amendments and Reauthorization Act STEL: Short-term Exposure Limits STOT: Specific Target Organ Toxicity TLV: Threshold Limit Value TSCA: Toxic Substances Control Act TWA: Time Weighted Average VOC: Volatile Organic Compounds WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com