

#### 1. IDENTIFICATION:

PRODUCT NAME: HENCO MASK TYPE I HMIS CODES H F R P

PRODUCT CODE: PHMTYI 2\*3 0 G

PRODUCT USE .: Low Friction Coating

#### Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300

INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800

NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

DATE PREPARED: 2/1/2016

#### 2. HAZARDS INDENTIFICATION



### CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2
Aspiration Hazard - Category 1
Carcinogenicity - Category 2
Serious Eye Irritation - Category 2A
Reproductive Toxicity - Category 1
Skin Irritation - Category 2
Specific target organ toxicity, single exposure - Category 3

### SIGNAL WORD:

DANGER

### HAZARDS STATEMENT:

H304-May be fatal if swallowed and enters airways

H315-Causes skin irritation

H319-Causes serious eye irritation

H335-May cause respiratory irritation

H351-Suspected of causing cancer

H360-May damage fertility or the unborn child.

H372-Causes damage to organs through prolonged and repeated exposure

### PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

P242-Use only non-sparking tools.

P280-Wear protective gloves/eye protection/face protection.

P403-P233-Store in well-ventilated place. Keep container tightly closed.

P501-Dispose of contents/container in accordance with

local/regional/national/regulation.



	SWLFII	DAIA		
ETHYL ACETATE			141-78-6	30% - 35%
ACGIH 400 ppm TWA				
NIOSH REL 400 ppm TWA				
NIOSH REL $1,400 \text{ mg/m3}$				
OSHA Z1 400 PPM TWA (1,4	00  mg/m3	)		
OSHA PO 400 ppm TWA (1,400	mg/m3)			
LD50 ORAL: 5620 mg/kg (rat	)			
LD LO INHALATION >22.5 mg/		6 hr		
LD50 DERMAL >20,000 mg/kg				
LC50 FISH 220 mg/l 96 hr	(IUDDIC)			
<del>_</del>	lo			
EC50 DAPHNIA 2,300 mg/l 24				
EC50 ALGAE 4,300 mg/l 24 h	r		0050 44 0	000
MINERAL SPIRITS			8052-41-3	20% - 25%
ACGIH TWA 100 ppm				
OSHA TWA 100 ppm				
PM ACETATE			108-65-6	0% - 5%
USWEEL TWA 50ppm				
LD50 ORAL 8,532 mg/kg (rat	)			
LD50: DERMAL >5000 mg/kg (				
LC50 FISH 100 mg/l 96h	I GDD I C /			
<del>_</del>				
EC50 DAPHNIA 500 mg/l 48h				
EC50 ALGAE 1,000 mg/l 96h				
AROMATIC NAPHTHA			64742-94-5	0% - 5%
ACGIH TWA 0.5 PPM SKIN				
LD50 INGESTION >2800 mg/k	g			
LD50 DERMAL $>5,000 \text{ mg/kg}$	Rabbit			
LD50 ORAL >5,000 mg/kg Rat				
LC50 FISH 10 mg/l 96hr				
EC50 DAPHNIA 10 mg/l 48 hr				
ErC50 ALGAE 2.5 MG/L 72 hr				
NAPHTHALENE			91-20-3	0° E°
			91-20-3	06 - 56
ACGIH TLV-TWA: 10 ppm				
ACGIH TLV STEL 15 PPM				
OSHA Z1 TWA-10 PPM				
OSHA Z1 TWA 50 mg/m3				
OSHA Z1 STEL 15 PPM				
OSHA Z1 STEL 75 mg/m3				
NIOSH REL TWA 10 PPM				
NIOSH REL TDWA 50 mg/m3				
LD50 ORAL RAT 2,000 mg/kg				
LC50 INHALATION RAT 1 HR >	340 mg/m3	3		
LD50 DERMAL RABBIT 2,500 m				
LC50 FISH 0.11 mg/l 96hr	9/129			
EC50 DAPHNIA 24.1 mg/l 48h				
ErC50 ALGAE 0.L4 mg/l 72hr				
CARBON BLACK			1333-86-4	0% - 5%
ACGIH-TLV: $3.0 \text{ mg/m}3 \text{ TWA}$ (	INHALABLE	Ξ)		
OSHA-PEL: 3.5 mg/m3 TWA				
LD50 ORAL: >8000 mg/kg (Ra	t)			
LC50 FISH >1,000 mg/l 96hr				
EC50 DAPHNIA >5,600 mg/l 2				
EC50 ALGAE >10,000 mg/l 72				
TOLUENE	111		108-88-3	NS - 58
			100 00 0	J 0
OSHA PEL 200.00 PPM-TWA	NC			
OSHA PEL 300.000 PPM-CEILI	МG			
OSHA VPEL 100.000 PPM-TWA	. ~			
OSHA VPEL 150.000 PPM-STEL				
ACGIH TLV 50.000 PPM-TWA (	SKIN)			



# SAFETY DATA SHEET

ACGIH TLV 150.000 PPM-STEL (SKIN)

LD 50 ORAL RAT: 2.6 g/kg

LC 50 INHALATION RAT: 8000 PPM; 4 h LD 50 DERMAL RABBIT: 12,124 mg/kg

LC50 FISH 7.63 mg/l 96 h

EC50 INVERTEBRATES 8 mg/l 24 h

EC50 ALGAE 10 mg/l 24h

### 4. First Aid Measures

#### Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

#### Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

#### Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

#### Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

### 5. Fire Fighting Measures

#### Flammable Properties:

Flash Point (Degree F) ..... 27 F
Flash Point Method ..... OPEN CUP

Explosive Limits:

Upper explosive limit: 11.5%(V) Lower explosive limit: 0.7.%

### Hazardous Combustion Products:

Carbon, Zinc, or their compounds

#### Extinguishing Media:

CO2, foam, dry chemical or halon

### Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

### 6. Accidental Release Measures

#### Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

#### Large Spill:

Remove by mechanical means and place in containers.



Use only non-sparking tools and equipment.

#### Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

### 7. Handling and Storage

#### Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

#### Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

#### 8. Exposure Controls/Personal Protection

#### Airborne Exposure Limits:

Mixture, see section 3

### Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

### Personal Protective Equipment:







### Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

#### Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

#### Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.



### SAFETY DATA SHEET

### 9. Physical and Chemical Properties

Flammability (solid, gas)....: Data not available

Boiling Point .....: 170 F

Melting Point .....: Data not available VOC.....: 679 grams/liter Freezing Point ....: Data not available

Flash Point ..... 27 F

Vapor Pressure .....: Data not available Vapor Density .....: Heavier than air. Solubility in Water .....: Slightly Soluble

Density....: 8.1 lb/gl

Evaporation Rate ...... Faster than n-Butyl Acetate.

Explosive Limits:

Upper Explosive Limit ....: 11.5%(V)
Lower Explosive Limit ....: 0.7.%
Specific Gravity ....: .97277
PH ....: None known

Volatile (% by Weight)....: 70%

Appearance and Odor .....: Black liquid, organic solvent odor

Odor Threshold ......: Not applicable
Viscosity .....: Not applicable
Partition Coefficient: ....: Data not available
Decomposition Temperature ...: Data not available
Autoignition temperature...: Data not available

### 10. Stability and Reactivity

#### Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

### Incompatibility:

Oxidizers, Strong Acids or Alkalies.

### Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Carbon, Zinc, or their compounds

### Hazardous Polymerization:

Will not occur.

### 11. Toxicological Information

### Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

### Germ Cell Mutagenicity:

None known

### Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer):
Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program):

Reasonably anticipated to be a human carcinogen

### Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

#### STOT-single exposure:



If inhaled may cause drowsiness or dizziness

#### STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration Hazard:

May be fatal if swallowed and enters airways

### Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

#### 12. Ecological Information

### Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

### Environmental Toxicity:

Data not available

### Persistence and Degradability:

Data not available

#### Bioaccumulative Potential:

Data not available

### Mobility in Soil

Data not available

#### Other Adverse Effects:

None known

#### 13. Disposal Considerations

### Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

### 14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

## UN Number:

UN 1263

### UN Shipping Name:

PAINT RELATED MATERIAL

### Transport Hazard Class:

Class 3





### Packing Group:

Group II

#### **ENVIRONMENTAL HAZARDS:**

#### Marine Pollutant:

None known

#### Special Precautions for User:

None known

### 15. Regulatory Information

### U.S. Federal Regulations:

#### OSHA:

OSHA Regulated

#### TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINCT FROM REQUIREMENTS

#### CERCLA: SARA Hazard Category:

### Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT CAS # % BY WT.

### FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

### State Regulations:

#### California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### International Regulations:

### WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)



### ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED

PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION

### REQUIRED BY THE CPR.

### EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

### 16. Other Information

Date of Preparation: 2/1/2016

### KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: International Carriage of Dangerous Goods by Road RID: International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act

DOT: Department of Transportation

HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IDL: Immediately Dangerous to Life

IMDG: International Maritime Dangerous Goods

IMO: International Maritime Organization

LC: Lethal Concentration

LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health

OSHA: Occupational Safety & Health Administration

PPM: Parts Per Million

REL: Recommended Exposure Limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limits STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

#### Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com