

1. IDENTIFICATION:

PRODUCT NAME: LUBE-LOK 4396 DILUTED

HMIS CODES H F R P

PRODUCT CODE: PLL4396D

2*3 0 G

PRODUCT USE.: Low Friction Coating

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300

INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800

NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

DATE PREPARED: 8/21/2019

2. HAZARDS IDENTIFICATION



CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2

Aspiration Hazard - Category 1

Carcinogenicity - Category 1

Serious Eye Irritation - Category 2

Germ Cell Mutagenicity - Category 1

Reproductive Toxicity - Category 1

Skin Corrosion/Irritation - Category 2

Specific target organ toxicity, repeated exposure - Category 2

Specific target organ toxicity, single exposure - Category 1

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H225-Highly flammable liquid and vapors

H304-May be fatal if swallowed and enters airways

H315-Causes skin irritation

H319-Causes serious eye irritation

H335-May cause respiratory irritation

H336-May cause drowsiness or dizziness

H340-May cause genetic defects

H350-May cause cancer

H360-May damage fertility or the unborn child.

H372-Causes damage to organs through prolonged and repeated exposure

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

SAFETY DATA SHEET

P242-Use only non-sparking tools.
 P280-Wear protective gloves/eye protection/face protection.
 P403-P233-Store in well-ventilated place. Keep container tightly closed.
 P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS#	% BY WT.
METHYL ETHYL KETONE	78-93-3	35% - 40%
ACGIH TLV: 200 ppm ACGIH STEL: 300 ppm NIOSH REL: TWA 200 ppm NIOSH REL: TWA 590 mg/m3 OSHA P0: TWA 200 ppm OSHA P0: TWA 590 mg/m3 OSHA P0: STEL 300 ppm OSHA P0 STEL 885 mg/m3 EC50 ALGAE ?100 mg/l 96 hr LD50 ORAL 3400.0 mg/kg (RATS) DC50 VAPORS 2000 PPM (RATS) LC50 FISH 100 mg/l 96 hr EC50 DAPHNIA >100 mg/l 48 hr		
METHYLENE CHLORIDE	75-09-2	35% - 40%
ACGIH: 50 PPM TWA OSHA: 25 PPM TWA OSHA STEL 125 PPM STEL OSHA ACTION LEVEL 12.5 PPM LC50 INHALATION: 52 mg/l 6h (rat) LD50 ORAL 1600 mg/kg (rats)		
TOLUENE	108-88-3	10% - 15%
OSHA PEL 200.00 PPM-TWA OSHA PEL 300.000 PPM-CEILING OSHA VPEL 100.000 PPM-TWA OSHA VPEL 150.000 PPM-STEL (SKIN) ACGIH TLV 50.000 PPM-TWA (SKIN) ACGIH TLV 150.000 PPM-STEL (SKIN) LD 50 ORAL RAT: 2.6 g/kg LC 50 INHALATION RAT: 8000 PPM; 4 h LD 50 DERMAL RABBIT: 12,124 mg/kg LC50 FISH 7.63 mg/l 96 h EC50 INVERTEBRATES 8 mg/l 24 h EC50 ALGAE 10 mg/l 24h		
ETHANOL	64-17-5	0% - 5%
OSHA PEL 1000.000 ppm TWA NIOSH REL 1,000 ppm TWA NIOSH REL 1,900 mg/m3 OSHA Z-1 1,000 ppm TWA OSHA Z-1 1,900 mg/m3 ACGIH 1,000 ppm STEL LD50 ORAL 7060 mg/kg (rat) LC 50 INHALATION 124.7 mg/l (rat) LC50 FISH 15,300 mg/l 96h EC50 DAPHNIA 5,012mg/l 48hr EC50 ALGAE 275 mg/l 72 hr		
N-METHYL-2-PYRROLIDONE	872-50-4	0% - 5%
ACGIH BEI: 100 mg/l US WEEL 10 ppm TWA LD50 ORAL-4150 mg/kg (rat) LC50 INHALATION->5.1 mg/l 4h		

SAFETY DATA SHEET

LD50 DERMAL: >5000 mg/kg (rat)		
LC50 FISH >100 mg/l 96h		
EC50 DAPHNIA >100 mg/l 24h		
EC50 ALGAE >100 mg/l 72h		
LC50 BACTERIA 9,000 mg/l		
ETHYLENE DICHLORIDE	107-06-2	0% - 5%
OSHA PEL-TWA: 50 ppm		
OSHA PEL-CEILING: 100 ppm		
ACGIH TWA: 10 ppm		
LD50 ORAL: 680 mg/kg (Rat)		
LD50 DERMAL: 4890 mg/kg (Rabbit)		
LC50 INHALATION 4 mg/l /6hr (Rat)		
LC50 FISH 136 mg/l 95 hr		
LC50 DAPHN IA 218 mg/l 48 hr		
EC50 ALGAE >433 mg/l 96 hr		
1,4 DIOXANE	123-91-1	0% - 5%
OSHA PEL 100 PPM SKIN		
OSHA PEL 360 mg/m3 SKIN		
ACGIH TWA: 20 PPM SKIN		
LD50 ORAL 5170 mg/kg (rat)		
LD50 DERMAL 7855 mg/kg (rabbit)		
LC0 INHALATION 38.8 mg/l (rat)		
LC50 FISH >199 ng.k 21 d		
EC50 DAPHNIA >1,000 mg/l 48 hr		
EC50 ALGAE >1,000 mg/l 72hr		

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point (Degree F) : 16F

Flash Point Method : TCC

Explosive Limits:

Upper explosive limit: 36.0

Lower explosive limit: 1.2

Hazardous Combustion Products:

Carbon, Hydrogen Sulfide, Sulfur oxide, or their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

SAFETY DATA SHEET

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:

SAFETY DATA SHEET



Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas).....: Data not available
 Boiling Point: 104 F
 Melting Point: Data not available
 VOC.....: 795 grams/liter
 Freezing Point: Data not available
 Flash Point: 16F
 Vapor Pressure: Data not available
 Vapor Density: Heavier than air.
 Solubility in Water: Slightly Soluble
 Density.....: 9. lb/gl
 Evaporation Rate: Faster than n-Butyl Acetate.
Explosive Limits:
 Upper Explosive Limit: 36.0
 Lower Explosive Limit: 1.2
 Specific Gravity: 1.08085
 PH: None known
 Volatile (% by Weight).....: 90%
 Appearance and Odor: Gray/Black liquid, organic solvent odor
 Odor Threshold: Not applicable
 Viscosity: Not applicable
 Partition Coefficient:.....: Data not available
 Decomposition Temperature ...: Data not available
 Autoignition temperature.....: Data not available

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released:
 Carbon, Hydrogen Sulfide, Sulfur oxide, or their compounds

Hazardous Polymerization:

Will not occur.

SAFETY DATA SHEET

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None known

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer):
Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program):

Known to be a human carcinogen

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

May cause respiratory irritation
May cause drowsiness or dizziness

STOT-repeated exposure:

Causes damage to organs through prolonged or repeated exposure
May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility.
Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1263

UN Shipping Name:

PAINT RELATED MATERIAL

Transport Hazard Class:

Class 3



Packing Group:

Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant:

None known

Special Precautions for User:

None known

15. Regulatory Information

U.S. Federal Regulations:

TSCA:

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.'

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINGUISHED FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
METHYLENE CHLORIDE	75-09-2	35% - 40%

SAFETY DATA SHEET

TOLUENE	108-88-3	10% - 15%
1-METHOXY-2-PROPANOL	107-98-2	0% - 5%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 8/21/2019

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists
 ADR: International Carriage of Dangerous Goods by Road
 RID: International Carriage of Dangerous Goods by Rail
 CAS: Chemical Abstracts Service
 CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act
 DOT: Department of Transportation
 HMIS: Hazardous Materials Identification System
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organization
 IDL: Immediately Dangerous to Life
 IMDG: International Maritime Dangerous Goods
 IMO: International Maritime Organization
 LC: Lethal Concentration
 LD: Lethal Dose
 NIOSH: National Institute for Occupational Safety & Health
 OSHA: Occupational Safety & Health Administration
 PPM: Parts Per Million
 REL: Recommended Exposure Limit
 SARA: Superfund Amendments and Reauthorization Act
 STEL: Short-term Exposure Limits
 STOT: Specific Target Organ Toxicity
 TLV: Threshold Limit Value

SAFETY DATA SHEET

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com