LUBRI-BOND 320R Page 1 of 9

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

1. IDENTIFICATION:

PRODUCT NAME: LUBRI-BOND 320R PRODUCT CODE: PLB320R PRODUCT USE.: Low Friction Coating Manufacturer: HMIS CODES H F R P 2*3 0 G

EVERLUBE PRODUCTS 100 COOPER CIRCLE PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300 INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800 NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR DATE PREPARED: 4/27/2021

2. HAZARDS INDENTIFICATION



CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2 Acute Toxicity, Dermal - Category 4 Acute Toxicity, Inhalation - Category 4 Acute Toxicity, Oral - Category 4 Carcinogenicity - Category 2 Serious Eye Irritation - Category 2 Reproductive Toxicity - Category 1 Respiratory Sensitization - Category 1 Skin Corrosion/Irritation - Category 2 Skin Sensitization - Category 1 Specific target organ toxicity, repeated exposure - Category 2 Specific target organ toxicity, single exposure - Category 3

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H225-Highly flammable liquid and vapors H302-Harmful if swallowed H312-Harmful in contact with skin. H315-Causes skin irritation H317-May cause an allergic skin reaction H319-Causes serious eye irritation H332-Harmful if inhaled H334-May cause allergy/asthma symptoms or breathing difficulties if inhaled H336-May cause drowsiness or dizziness H351-Suspected of causing cancer H360-May damage fertility or the unborn child. H373-May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

EVERLUBE PRODUCTS SAFETY DATA SHEET

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking P242-Use only non-sparking tools. P280-Wear protective gloves/eye protection/face protection. P403-P233-Store in well-ventilated place. Keep container tightly closed. P501-Dispose of contents/container in accordance with local/regional/national/regulation.

| 3. COMPOSITION/INFORMATION ON INGREDIENTS | CAS# १ | BY WT. |
|---|-----------|-----------------|
| ETHYL ACETATE | 141-78-6 | 55 - 60% |
| ACGIH 400 ppm TWA | | |
| NIOSH REL 400 ppm TWA | | |
| NIOSH REL 1,400 mg/m3 | | |
| OSHA Z1 400 PPM TWA (1,400 mg/m3) | | |
| OSHA PO 400 ppm TWA (1,400 mg/m3) | | |
| LD50 ORAL: 5620 mg/kg (rat) | | |
| LD LO INHALATION >22.5 mg/l (rat) 6 hr | | |
| LD50 DERMAL >20,000 mg/kg (rabbit) | | |
| LC50 FISH 220 mg/l 96 hr | | |
| EC50 DAPHNIA 2,300 mg/l 24 hr | | |
| EC50 ALGAE 4,300 mg/l 24 hr | | |
| PM ACETATE | 108-65-6 | 10% - 15% |
| USWEEL TWA 50ppm | | |
| LD50 ORAL 8,532 mg/kg (rat) | | |
| LD50: DERMAL >5000 mg/kg (rabbit) | | |
| LC50 FISH 100 mg/l 96h | | |
| EC50 DAPHNIA 500 mg/l 48h | | |
| EC50 ALGAE 1,000 mg/l 96h | | |
| XYLENE | 1330-20-7 | 5% - 10% |
| ACGIH TWA: 100 PPM | | |
| ACGIH STEL: 150 PPM | | |
| OSHA Z-1 TWA: 100 PPM | | |
| OSHA Z-1 435 mg/m3 | | |
| LD50: ORAL 3,523 mg/kg (rat) | | |
| LC50 INHALATION 6700 ppm (rat) 4hr | | |
| EC50 ALGAE 4.36 mg/l 73 hr | | |
| IC50 DAPHNIA 1 mg/l 24hr LC50 FISH 2.6 mg/l 96hr | | |
| ETHYL BENZENE | 100-41-4 | 08 - 58 |
| ACGIH: 20 ppm TWA | 100 11 1 | 0 0 0 0 0 |
| OSHA 100 ppm TWA; 435 mg/m3 TWA | | |
| OSHA 125 ppm STEL; 545 mg/m3 STEL | | |
| NIOSH 100 ppm TWA; 435 mg/m3 TWA | | |
| NIOSH 125 ppm STEL; 545 mg/m3 STEL | | |
| LD50 ORAL: 3500 mg/kg (rat) | | |
| LC50 Inhalation 17.2 mg/l 4h (rat) | | |
| LD50 Dermal 15354 mg/kg (rabbit) | | |
| LC50 FISH: 11.0-18.0 mg/l 96 hr | | |
| EC50 ALGAE 4.6 mg/l 72 hr | | |
| EC50 DAPHNIA 182.5 mg/l 48 hr | | |
| CARBON BLACK | 1333-86-4 | 0% - 5% |
| ACGIH-TLV: 3.0 mg/m3 TWA (INHALABLE) | | |
| OSHA-PEL: 3.5 mg/m3 TWA | | |
| LD50 ORAL: >8000 mg/kg (Rat) | | |
| LC50 FISH >1,000 mg/l 96hr | | |
| EC50 DAPHNIA >5,600 mg/l 24 hr | | |
| EC50 ALGAE >10,000 mg/l 72 hr | | |
| METHYL ISOBUTYL KETONE | 108-10-1 | 0% - 5% |
| ACGIH TWA: 20 ppm | | |

LUBRI-BOND 320R Page 3 of 9

EVERLUBE[®] **PRODUCTS** SAFETY DATA SHEET

ACGIH STEL: 75 ppm NIOSH REL: 50 ppm NIOSH REL: 205 mg/m3 NIOSH STEL: 75 ppm NIOSH STEL: 300 mg/m3 OSHA Z1-TWA100 ppm OSHA Z1-410 mg/m3 OSHA PO-TWA 50 ppm OSHA P0-205 mg/m3 OSHA PO-stel 75 ppm OSHA 300 mg/m3 LD50 RAT ORAL: 2080 mg/kg LD50 INHALATION RAT: >2000 PPM, 4 hr LC50 RAT INHALATION 8.L2-16.4 mg/l LC50 FISH >179 mg/l 96h EC50 AQUATIC INVERTEBRATES >200 mg/l 48h EC50 ALGAE 400 mg/l 95h 96-29-7 08 - 58 ANTI-SKINNING AGENT LD/50 3680 mg/kg rat oral LD50 1-2 ml/kg Skin Rabbit COBALT CARBOXYLATE 136-52-7 0% - 5% ACGIH TLV-TWA: 0.02 mg/m3 OSHA PEL: TWA 0.01 mg/m3 LD50 ORAL: >2000 mg/kg (rat)

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties: Flash Point (Degree F) 25 F Flash Point Method OPEN CUP Explosive Limits: Upper explosive limit: 11.5%(V) Lower explosive limit: 1.0% (V)

Hazardous Combustion Products:

Carbon, Fluorine, or their compounds

Extinguishing Media: CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full



protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits: Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:





Respiratory Protection:

In case of inadequate ventilation, wear respirator protection. Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

| Flammability (solid, gas): Boiling Point | |
|---|---|
| Melting Point | |
| VOC | |
| Freezing Point | - |
| Flash Point | 25 F |
| Vapor Pressure | Data not available |
| Vapor Density | Heavier than air. |
| Solubility in Water | Slightly Soluble |
| Density: | 7.5 lb/gl |
| Evaporation Rate | Faster than n-Butyl Acetate. |
| Explosive Limits: | |
| Upper Explosive Limit: | |
| Lower Explosive Limit: | 1.0% (V) |
| Specific Gravity | .90071 |
| РН: | None known |
| Volatile (% by Weight) | 80% |
| | Black liquid, characteristic ester odor |
| Odor Threshold | |
| Viscosity: | |
| Partition Coefficient: | |
| Decomposition Temperature: | |
| Autoignition temperature: | Data not available |

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid): Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Carbon, Fluorine, or their compounds

Hazardous Polymerization:

Will not occur.

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

11. Toxicological Information

Acute Toxicity Values: Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None known

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer): Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): None known

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

May cause drowsiness or dizziness

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be harmful if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information

Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability: Data not available

Data not avallable

Bioaccumulative Potential:

Data not available

Mobility in Soil Data not available

Other Adverse Effects: None known

13. Disposal Considerations

Disposal Methods:

EVERLUBE PRODUCTS

Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1263

UN Shipping Name:

PAINT RELATED MATERIAL

Transport Hazard Class:

Class 3



Packing Group: Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant: None known

Special Precautions for User: None known

15. Regulatory Information

U.S. Federal Regulations:

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXEMPT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

| COMPONENT | CAS # | % BY WT. |
|---------------|-----------|-----------------|
| ETHYL ACETATE | 141-78-6 | 55 - 60% |
| PM ACETATE | 108-65-6 | 10% - 15% |
| XYLENE | 1330-20-7 | 5% - 10% |
| ETHYL BENZENE | 100-41-4 | 0% - 5% |
| CARBON BLACK | 1333-86-4 | 0% - 5% |

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT



MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 4/27/2021

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists ADR: International Carriage of Dangerous Goods by Road RID: International Carriage of Dangerous Goods by Rail CAS: Chemical Abstracts Service CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act DOT: Department of Transportation HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization IDL: Immediately Dangerous to Life IMDG: International Maritime Dangerous Goods IMO: International Maritime Organization LC: Lethal Concentration LD: Lethal Dose NIOSH: National Institute for Occupational Safety & Health OSHA: Occupational Safety & Health Administration PPM: Parts Per Million REL: Recommended Exposure Limit SARA: Superfund Amendments and Reauthorization Act STEL: Short-term Exposure Limits STOT: Specific Target Organ Toxicity TLV: Threshold Limit Value TSCA: Toxic Substances Control Act TWA: Time Weighted Average VOC: Volatile Organic Compounds WHMIS: Workplace Hazardous Materials Information System

EVERLUBE[®] PRODUCTS SAFETY DATA SHEET

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com